



Crosse KCR : en aluminium, Ø 60 mm


Fixation du luminaire en coiffant ou pénétrant standard Eclatec (cf p.132)

Fixation coiffante de la crosse sur le mât


Finition : thermolaquage par poudrage polyester, couleur au choix

Mât : acier cylindro-conique Ø 60/62 mm


KCR	A mm	B mm	C mm	D mm	Inclinaison degrés	Poids kg	SCx m ²
Simple feu	750	445	-	-	15	4	0,05
Double feu	750	445	1498	-	15	5,7	0,07
Applique murale	750	345	-	200	15	3,4	0,04
Contre-feu	750	345	-	200	15	3,4	0,04




crosse KCR simple feu



crosse KCR double feu



applique murale KCR



Contre-feu KCR



Chorus KCR



Elipt KCR



Tilt T KCR



Tsana KCR



Murena KCR



Tsana X KCR



Enza KCR



Zelda KCR



Zesto KCR



Paleo KCR

LED Luminaires

Modern Streetfurniture

Waste bins

Bollards Light

tree grill

Bollards

Classic poles cast iron

Steel poles

MODERN POLES CAST IRON

Defence bollards

Drinkwater fountain

SEATING

TRAMWAY POLES

Modern LED luminaires

Classic luminaires

Classic street furniture

Ghm

Rue Antoine Durenne
52220 Sommevoire
France
Tel nr. 0033 3 25 55 23 03

ECLATEC

41 rue Lafayette
54320 Maxeville
France
Tel nr. 0033 3 83 39 38 28

Export internet : www.ghm-eclatec.com

Email export: info@ghm-eclatec.com